

Single Phase, TEFC, Foot Mounted

1/12 thru 15 Hp

NEMA 42 thru 254T

Applications: Compressors, pumps, fans, farm equipment, conveyors, material handling equipment, machine tools and others.

Features: Heavy gauge steel frames and a heavy duty base seam welded to the frame, ball bearings, a "Snap Action" starting switch and gasketed conduit box and capacitor cover.



General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
.08	1800	42	L3351	249	K	9.56	15	44	115/230	1	3,30	
	3600	42	L3352	255	K	9.56	15	45	115/230	1.25	3,30	
	1800	42	L3353	258	K	9.56	16	47	115/230	1.55	3,30	
1/6	3600	42	L3354	267	K	9.56	16	52	115/230	1.6	3,30	
	1800	42	L3355	282	K	9.56	18	51	115/230	1.8	3,30	
		48	L3400	281	K	10.73	18	49	115/230	1.9	3,30	
	1200	48	L3401	397	K	10.73	23	47	115/230	2.3	3,30	
1/4	3600	42	L3356	285	K	9.56	18	57	115/230	2	3,30	
	1800	48	EL3403	353	K	10.48	24	74	115/230	1.25	1,65	
		48	L3403	289	K	10.73	20	55	115/230	2.5	3,30	
		48	L3403M	331	K	10.73	20	55	115/230	2.5	3,30	
	1200	48	L3404	423	K	11.35	26	48	115/230	3.2	3,30	
		56	L3500	444	K	12.25	27	47	115/230	3	3,30	
1/3	3600	48	L3405	263	K	10.73	20	55	115/208-230	3	3,30	
	1800	48	L3406	306	K	10.73	21	60	115/230	3	3,30	
		48	L3406M	348	K	10.73	22	60	115/230	3	3,30	
		56	EL3501	390	K	11.97	28	77	115/230	1.6	1,65	
		56	L3501	297	K	11.35	22	60	115/230	3	3,30	
	1200	56	L3501M	348	K	11.35	22	60	115/230	3	3,30	
		48	L3407	465	K	11.35	27	54	115/230	3.7	3,30	
	1/2	3600	56	L3502	465	K	11.97	29	54	115/230	3.7	3,30
48			L3408	298	K	10.73	21	66	115/230	3.5	3,30	
56			L3503	298	K	11.35	22	66	115/230	3.5	3,30	
1800			48	L3409	341	K	11.35	26	68	115/230	3.7	3,30
			48	L3409M	409	K	11.35	27	68	115/230	3.7	3,30
			56	EL3504	460	K	11.97	30	78.5	115/230	2.3	1,65
		56	L3504	348	K	11.97	27	68	115/230	3.7	3,30	
1200		56	L3504A	416	K	11.97	27	68	115/230	3.7	3,30	
		56	L3504M	409	K	11.97	27	68	115/230	3.7	3,30	
3/4		56H	L3505	660	K	12.93	39	59	115/230	4	3,30,36	
		3600	56	L3506	335	K	11.97	29	66	115/230	4.8	3,30
			1800	56	EL3507	560	K	13.25	41	82.5	115/230	3.15
	56			L3507	401	K	12.47	34	72	115/230	4.2	30,65
	56			L3507A	503	K	12.47	34	74	115/230	4.1	30,65
	56			L3507M	481	K	12.47	34	74	115/230	4.1	30,65
	1200		56H	L3508	763	K	12.93	41	68	115/230	5	2,30,36,65
		143T	L3508T	751	L1	13.30	41	68	115/230	5	2,30,65	

(a) See notes on inside back flap and pages 5-6.

Single Phase, TEFC, Foot Mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1	3600	56H	L3509	388	K	12.93	37	68	115/230	5.9	3,30,36
		56H	L3509M	439	K	12.93	40	66	115/230	6	3,36
	1800	56H	L3510A	565	K	12.93	37	67	115/230	6.5	3,30,36
		56H	L3510M	546	K	12.93	37	67	115/230	6.5	3,30,36
		56H	EL3510	643	K	13.81	44	82.5	115/230	4.25	1,36,65
		56H	L3510	455	K	12.93	40	67	115/230	6.4	3,30,36
		143T	L3510T	464	L1	13.31	37	67	115/230	6.4	3,30
		143T	L3510TM	546	L1	13.31	37	67	115/230	6.5	3,30
	182	L3601	838	L1	14.31	54	72	115/230	6	3,30	
	1200	184	L3607	1,339	L1	15.69	71	67	115/230	7	3,30
1 1/2	3600	56H	L3513	520	K	12.93	41	70	115/230	8	3,30,36
		56H	L3513M	596	K	12.93	45	70	115/230	7.5	2,3,36
		143T	L3513T	511	L1	13.31	41	70	115/230	8	3,30
	1800	56H	EL3514	733	K	15.18	57	84	115/230	6.3	1,36,65
		56/56H	L3514	526	K	13.81	48	75.5	115/230	8	30,36,65
		56/56H	L3514A	670	K	13.81	45	75.5	115/230	8	2,36,65
		56/56H	L3514M	617	K	13.81	50	75.5	115/230	8	2,36,65
		145T	EL3514T	733	L1	15.55	57	84	115/230	6.3	1,65
		145T	L3514T	534	L1	14.18	48	75.5	115/230	8	30,65
	145T	L3514TM	617	L1	14.19	48	75.5	115/230	8	2,65	
184	L3603	913	L1	15.69	66	70	115/230	9.5	3,30		
1200	184T	L3613T	1,395	L1	16.56	75	73	115/230	8.2	1,30,65	
2	3600	56H	L3515	664	K	13.81	54	74	115/230	11.5	1,3,30,36
		56H	L3515M	696	K	13.81	51	74	115/230	11.5	2,3,36
		145T	L3515T	670	L1	14.19	51	74	115/230	11.5	1,3,30
	1800	56HZ	L3516TM	877	K	14.18	48	78	230	8.3	1,57,65
		145T	L3516T	853	L1	14.19	48	78	115/230	8.3	1,65
		182T	L3605T	762	L1	16.56	67	75.5	115/230	11.5	3,30
		182T	L3605TM	929	L1	16.56	71	75	115/230	11	2,3
		184T	EL3605T	1,003	L1	16.56	64	82.5	115/230	8.8	1,65
		184	L3605	1,022	L1	15.69	66	75.5	115/230	11.5	3,30
	184	L3605M	1,095	L1	15.69	67	75.5	115/230	11.5	3,30	
1200	215	L3703	2,211	L1	17.51	114	80	115/230	9.4	2,30,65	
3	3600	182T	L3606T	786	L1	16.56	73	76	115/230	14.5	1,3,30
		184	L3606	1,442	L1	15.69	70	76	115/230	14.5	1,3,30
	1800	184T	EL3609T	1,170	L1	18.06	90	85.5	230	11.8	1,65
		184T	L3609T	897	L1	16.56	79	78	115/230	14	2,20,30,65
		184T	L3609TM	969	L1	16.54	76	78	115/230	14.5	2,20,65
	215	L3705	1,743	L1	17.51	116	80	115/230	14	30,65	
1200	215	L3706	2,655	L1	17.51	132	82.5	115/230	14	1,30,65	
5	3600	184T	L3608T	1,082	L1	18.06	89	83	230	19.5	2,20,65
		184T	L3608TM	1,116	L1	18.05	86	83	230	19.5	2,20,65
	1800	184T	EL3612T	1,396	L1	18.06	96	86.5	230	19.1	2,20,65
		184T	L3612TM	1,127	L1	18.05	99	80	230	23	2,20,65
		213T	L3708T	1,069	L1	19.02	117	84	230	20.5	1,30,65
		213T	L3708TM	1,257	L1	19.02	135	82	230	21.5	2,65
215	L3708	1,782	L1	18.64	130	84	230	20.5	1,30,65		
7 1/2	3600	213T	L3709T	1,393	L1	17.89	121	83	230	33	2,30,65
	1800	215T	L3710T	1,413	L1	19.02	138	86.5	230	29	2,20,30,65
10	3600	215T	L3711T	1,709	L1	19.02	145	82	230	40	2,20,65
	1800	215T	L3712T	1,734	L1	20.52	161	86.5	230	38	2,5,20,65
15	1800	254T	L1177T	4,941	L1	23.16	322	86.5	230	60	2,20,65

(a) See notes on inside back flap and pages 5-6.

■ Cast Iron Frame

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors

BALDOR • RELIANCE

Single Phase, TEFC, C-Face, No Drip Cover

1/6 thru 10 Hp

NEMA 56C thru 215TC

Applications: Pumps, fans, conveyors, machine tools, gear reducers and other applications requiring a NEMA C-face motor.

Features: Pressure cast aluminum end plates with ribbed design for rigidity. Ball bearings with a locked drive end bearing, heavy-gauge steel frame, and gasketed conduit box and capacitor cover.



General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
C-Face, Foot Mounted											
1/4	1800	56C	CL3403	305	K	11.48	21	55	115/208-230	2.5	3
1/3	3600	56C	CL3405	304	K	11.48	21	55	115/208-230	3	3
	1800	56C	CL3501	319	K	11.35	23	60	115/230	3	3,30
1/2	3600	56C	CL3503	320	K	11.35	24	66	115/230	3.5	3,30
	1800	56C	CL3504	372	K	11.97	28	68	115/230	3.7	3,30
3/4	3600	56C	CL3506	356	K	11.97	29	66	115/230	4.8	3,30
	1800	56C	CL3507	445	K	12.47	35	72	115/230	4.2	30,65
1	3600	56C	CL3509	411	K	12.25	37	68	115/230	5.9	3,30
	1800	56C	CL3510	502	K	13.25	40	67	115/230	6.4	3,30
1 1/2	3600	56C	CL3513	533	K	13.25	44	70	115/230	7.5	3,30
		56C	CL3514	596	K	14.12	49	70	115/230	7.5	30,65
2	3600	56C	CL3515	686	K	14.12	52	74	115/230	11.5	1,3,30
		145TC	CL3515T	692	L1	14.19	53	74	115/230	11.5	1,3,30
3	1800	184TC	CL3619TM	1,152	L1	16.54	81	81.5	230	13.2	2,20
		3600	184TC	CL3608TM	1,247	L1	18.05	91	83	230	19.5
5	1800	184TC	CL3612TM	1,207	L1	18.05	101	80	230	23	2,20
		3600	215TC	CL3711T	2,029	L1	19.75	167	82	230	40
10	1800	215TC	CL3712T	2,052	L1	21.25	163	86.5	230	38	2,20
		215TC	CL3712T	2,052	L1	21.25	163	86.5	230	38	2,20
C-Face, Footless											
1/6	1800	56C	KL3400	297	K	11.35	18	49	115/230	1.9	3,30
	1200	56C	KL3401	415	K	11.35	23	47	115/230	2.3	3,30
1/4	1800	56C	KL3403	305	K	11.35	20	55	115/230	2.5	3,30
		56C	KL3405	281	K	11.35	21	55	115/208-230	3	3
1/3	3600	56C	KL3405	282	K	11.48	258	—	115/208-230	3	3
		1800	56C	VL3501	313	K	11.35	22	60	115/230	3
1/2	3600	56C	VL3503	316	K	11.35	21	66	115/230	3.5	3,30
		1800	56C	VL3504	365	K	11.97	27	68	115/230	3.7
3/4	1200	56C	VL3505	677	K	13.25	41	59	115/230	4	3,30
		3600	56C	VL3506	351	K	11.97	29	66	115/230	4.8
1	3600	56C	VL3506A	388	K	11.97	28	66	115/230	4.8	3
		1800	56C	VL3507	419	K	12.47	34	72	115/230	4.2
1 1/2	1200	56C	VL3508	779	K	13.25	41	68	115/230	5	2,30,65
		3600	56C	VL3509	405	K	12.25	36	68	115/230	5.9
2	3600	56C	VL3509A	442	K	13.25	40	66	115/230	6	3
		1800	56C	VL3510	480	K	13.25	38	67	115/230	6.4
3	1800	143TC	VL3510T	480	L1	13.31	39	67	115/230	6.4	3,30
		3600	56C	VL3513	527	K	13.25	40	70	115/230	8
1 1/2	143TC	VL3513T	559	L1	13.31	41	70	115/230	8	3,30	
		1800	56C	VL3514	544	K	14.12	47	75.5	115/230	8
2	145TC	VL3514T	550	L1	14.18	47	75.5	115/230	8	30,65	
		3600	56C	VL3515	674	K	14.12	51	74	115/230	11.5
3	1800	145TC	VL3515T	686	L1	14.19	50	74	115/230	11.5	1,3,30
		182TC	VL3605T	974	L1	16.55	66	75.5	115/230	11.5	3,30
1 1/2	1800	184C	VL3605	1,102	L1	15.68	62	75.5	115/230	11.5	3,30
		3600	182TC	VL3606T	1,087	L1	16.55	71	76	115/230	14.5
2	1800	184TC	VL3609T	1,150	L1	16.55	76	78	115/230	14	2,20,30,65

(a) See notes on inside back flap and pages 5-6.

**Single Phase,
ODP, Foot Mounted**

1/6 thru 10 Hp

NEMA 48 thru 215T

Applications: Compressors, pumps, conveyors, machine tools, air handling, and others.

Features: Copper windings, dynamically balanced rotors, ball bearings, heavy-gauge steel frames, and other industrial quality features.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
1/6	1800	48	L1200	235	K	9.13	18	49	115/230	1.9	30	
	1200	48	L1201	359	K	9.38	23	47	115/230	2.3	30	
1/4	1800	48	EL1203	306	K	9.76	23	74	115/230	1.25	1,65	
		48	L1203	238	K	9.13	19	59.5	115/230	2.2	30	
		48	L1203M	274	K	9.13	20	55	115/230	2.5	30	
	1200	48	L1204	384	K	9.75	25	48	115/230	3.2	30	
		56	L1300	399	K	10.13	26	48	115/230	3.2	30	
		56	L1300M	399	K	10.13	26	48	115/230	3.2	30	
1/3	3600	48	L1205	225	K	9.13	20	55	115/208-230	3	30	
		48	L1206	274	K	9.13	21	60	115/230	3	30	
	1800	48	L1206M	308	K	9.13	22	60	115/230	3	30	
		56	EL1301	363	K	10.13	26	77	115/230	1.6	1,65	
		56	L1301	277	K	9.51	22	60	115/230	3	30	
		56	L1301M	324	K	9.51	22	60	115/230	3	30	
	1200	48	L1207	409	K	10.63	28	54	115/230	3.7	30	
		56	L1302	409	K	11.01	29	54	115/230	3.7	30	
	1/2	3600	48	L1208	249	K	9.13	22	57	115/230	3.7	30
			56	L1303	249	K	9.51	21	66	115/230	3.5	30
1800		48	L1209	344	K	9.75	24	68	115/230	3.7	30	
		48	L1209M	383	K	9.38	24	62	115/230	4.2	30	
		56	EL1304	415	K	11.00	29	78.5	115/230	2.3	1,65	
		56	L1304	306	K	9.76	24	68	115/230	3.7	30	
		56	L1304A	364	K	9.76	25	62	115/230	4.2	30	
		56	L1304M	383	K	9.76	25	62	115/230	4.2	30	
1200		56H	L1305	616	K	11.75	38	62	115/230	4.1	30,36	
3/4		3600	56	L1306	304	K	12.85	26	72	115/230	4.7	30
	56		L1306A	320	K	11.75	29	69	115/230	5.5		
	1800	56	EL1307	512	K	12.06	35	84	115/230	3.25	1,65	
		56	L1307	378	K	11.51	32	68	115/230	5.1	30	
		56	L1307A	444	K	11.51	32	68	115/230	5.1	30	
		56	L1307M	455	K	11.51	32	68	115/230	5.1	30	
	1200	56H	L1308	693	K	11.75	42	68	115/230	5	30,36,65	
	1	3600	56	L1309	319	K	11.01	31	65	115/230	7.5	30
56			L1309A	340	K	11.01	30	70	115/230	6.6		
1800		56H	L1318	452	K	11.75	39	67	115/230	6.2	30,36	
		56H	L1318M	492	K	11.75	39	67	115/230	6.2	2,36	
		56	EL1310	557	K	12.94	40	84	115/230	4.3	1,65	
		56	L1310	413	K	11.07	34	66	115/230	6.7	30	
		56H	L1310M	529	K	11.75	36	66	115/230	6.7	30,36	
		143T	L1318T	471	L1	13.00	42	67	115/230	6.2	30	
		143T	L1318TM	492	L1	12.12	39	67	115/230	6.2	2	
		182	L1401	672	L1	12.75	50	70	115/230	7	30	
		182	L1401M	729	L1	12.75	48	70	115/230	7		
		1200	184	L1407	1,179	L1	14.13	63	65	115/230	8	30

(a) See notes on inside back flap and pages 5-6.

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors

BALDOR • RELIANCE
Single Phase, ODP, Foot Mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)		
1 1/2	3600	56H	L1313A	468	K	11.75	40	68	115/230	9	30,36		
		56H	L1313	448	K	11.75	34	80	115/230	6.4	30,36,65		
		143T	L1313T	448	L1	11.12	37	70	115/230	8.9	30		
	1800	56H	L1319	534	K	11.75	41	68	115/230	9	30,36		
		56H	L1319M	595	K	11.75	39	68	115/230	9	36		
		56H	EL1319	730	K	14.00	47	85.5	115/230	6.25	1,36,65		
		145T	EL1319T	757	L1	13.00	49	85.5	115/230	6.25	1,65		
		145T	L1319T	504	L1	12.12	39	68	115/230	9	30		
		145T	L1321T	605	L1	13.00	45	70	115/230	10.5	30		
		145T	L1321TM	656	L1	13.00	45	70	115/230	10.5			
		184	L1403	750	L1	12.75	56	68	115/230	9.5	30		
		184	L1403M	795	L1	12.75	56	68	115/230	9.5			
		2	3600	56H	L1317	595	K	11.75	43	70	115/230	13	30,36
				56H	L1317A	612	K	11.75	40	70	115/230	12	30,36
145T	L1320T			638	L1	12.12	46	71	115/230	11.5	30,65		
1800	145T		L1322T	617	L1	13.00	48	75.5	115/230	10.2	65		
	145T		L1322TM	671	L1	13.00	45	78.5	115/230	9.2	65		
	182T		EL1405T	854	L1	15.87	65	82.5	115/230	8.8	1,65		
	182T		L1405T	633	L1	15.00	65	71	115/230	12	30		
	184		L1405	788	L1	14.13	64	71	115/230	12	30		
	213		L1502	1,353	L1	14.32	82	69	115/230	12.5	30		
	1200		215	L1503	1,842	L1	15.94	104	68	115/230	14	30	
	3		3600	182T	L1406T	726	L1	15.00	65	78	115/230	14	30
184T				EL1408T	894	L1	16.50	78	85.5	230	11.2	1,65	
1800			184T	L1408T	684	L1	15.00	73	78	115/230	16	30,65	
			184T	L1408TM	806	L1	15.00	78	78	115/230	16	65	
		215	L1505	1,499	L1	15.94	102	75	115/230	18	30		
		1200	215	L1506	2,153	L1	15.94	111	75	115/230	16	30,65	
5	3600	184T	L1409T	863	L1	15.00	76	75	230	23	30		
		184T	EL1410T	1,021	L1	18.00	95	86.5	230	19.1	1,65		
	1800	184T	L1410T	810	LS	16.50	86	82.5	230	23	1,30,65		
		184T	L1410TM	981	L1	16.50	84	82.5	230	23	1,30,65		
		184T	L1430T	743	L1	16.55	79	84	230	20.6	1,30,65		
		184T	L1430TM	981	L1	16.55	84	80	230	24	1,30,65		
		213T	L1508T	1,069	L1	16.32	113	77	230	27			
7 1/2	3600	213T	L1509T	1,334	L1	18.37	101	82.5	230	30	1,30,65		
	1800	215T	L1510T	1,161	L1	17.45	134	85.5	230	31	30,65		
10	3600	215T	L1511T	1,683	L1	17.45	130	83	230	46	1,30		
	1800	215T	L1512T	1,695	L1	17.45	140	85.5	230	39	2,65		

(a) See notes on inside back flap and pages 5-6.

General Information

Premium Efficient Super-E@ Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors

**Single Phase,
ODP, C-Face**

1/6 thru 5 Hp

NEMA 56C thru 184TC

Applications: Pumps, fans, conveyors, machine tools, gear reducers and other applications requiring a NEMA C-face motor.

Features: Pressure cast aluminum end plates with ribbed design for rigidity. Ball bearings with a locked drive end bearing, heavy-gauge steel frame.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
C-Face, Foot Mounted, No Drip Cover											
1/3	1800	56C	CL1301	310	K	10.10	23	60	115/230	3	30
1/2	3600	56C	CL1303	275	K	10.06	22	66	115/230	3.5	30
	1800	56C	CL1304	353	K	10.35	25	62	115/230	4.2	30
3/4	1800	56C	CL1307	405	K	12.06	34	68	115/230	5.1	30
1	1800	56C	CL1310	465	K	11.06	31	66	115/230	6.7	30
3	1800	184TC	CL1408TM	852	L1	15.00	78	78	115/230	16	65
5	1800	184TC	CL1410TM	1,026	L1	16.50	88	82.5	230	23	1,30,65
C-Face, Foot Mounted, Drip Cover											
5	1800	184TC	CL1430TM	1,026	L1	16.55	84	80	230	24	1,30,65
C-Face, Footless, Drip Cover											
1/6	1800	56C	KL1200	251	K	11.22	18	49	115/230	1.9	30
1/4	1800	56C	KL1203	256	K	11.22	20	55	115/230	2.5	30
1/3	3600	56C	KL1205	243	K	11.22	21	55	115/208-230	3	30
		56C	KL1205A	249	K	11.35	21	55	115/230	3	30
	1800	56C	VL1301	294	K	11.22	22	60	115/230	3	30
1/2	3600	56C	VL1303	267	K	11.22	21	66	115/230	3.5	30
	1800	56C	VL1304	323	K	11.47	24	62	115/230	4.2	30
	1200	56C	VL1305	633	K	13.24	36	62	115/230	4.1	30
3/4	3600	56C	VL1306	320	K	12.85	27	72	115/230	4.7	30
	1800	56C	VL1307	395	K	13.22	33	68	115/230	5.1	30
	1200	56C	VL1308	709	K	13.24	43	68	115/230	5	30
1	3600	56C	VL1309	336	K	12.72	32	65	115/230	7.5	30
	1800	56C	VL1310	430	K	12.24	34	66	115/230	6.7	30
		56C	VL1318	468	K	13.24	42	67	115/230	6.2	30
1 1/2	3600	56C	VL1313	465	K	12.73	32	80	115/230	6.4	30
	1800	56C	VL1319	550	K	13.24	42	68	115/230	9	30
		145TC	VL1321T	622	L1	14.18	49	70	115/230	10.5	30
2	3600	56C	VL1317	612	K	13.24	43	70	115/230	13	30
	1800	145TC	VL1322T	634	L1	14.18	47	75.5	115/230	10.2	65
3	3600	182TC	VL1406T	770	L1	15.18	59	75.5	115/230	13.6	30,65
	1800	184TC	VL1408T	780	L1	16.55	76	78	115/230	16	30,65

(a) See notes on inside back flap and pages 5-6.

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors